



Engineered for comfort and safety, Aurora Rx uses patented itsTRU[®] technology to fusion-bond a PUR-coated calendered rubber surface layer to 5 mm of VCR backing. This two-layered PVC-free surface is manufactured to reduce the severity of fall-related injuries while mitigating liability. Ergonomic and quiet underfoot, Aurora Rx creates a more comfortable space to work.

Markets

- Corporate
- Education

Applications

- Multipurpose Courts
- Locker / Restrooms
- Common Areas
- Medical / Acute Care
- Clinical / Labs
- Therapy / Rehab
- Retail
- Entrances
- Childcare / Playzones

Benefits

- PUR-coated
- Hygienic because of heat-welded installation
- Quiet underfoot
- Ergonomic
- Colors create more calming, peaceful healing and learning environments

Product Information

Nominal Dimensions:

Available as a standard in rolls. Talk to your local agent to determine availability, pricing, minimums, and lead times.



Rolls:
58" (1.47 m)
Thickness: 7 mm nominal
(2 mm surface layer + 5 mm VCR base layer)

[View Colors](#)

THE NRG FACTOR

NRG

=

11.2%

Force Reduction

Absorption of impact energy

67.4%

Energy Restitution

Useful return of impact energy

Safety

Ergonomics

Acoustics

Technical Details

Performance Criteria	Test Standard	Typical Results
Recovery after Static Load	ASTM F970	0.003"
Recovery after Static Load (@1000 psi after 96 hrs)	ASTM F970 Modified	0.003"
Coefficient of Friction	ASTM D2047	≥ 0.6
VOC Compliant	CA01350	Pass
Flammability - Critical Radial Flux	ASTM E648	Class I
Smoke Development	ASTM E662	Pass
Abrasion Resistance	ASTM D3389	Pass
G-Max	ASTM F355	721
Antimicrobial Resistance Test	ASTM G21	Pass
Resistance to Light	ASTM F1515	Pass
Resistance to Heat	ASTM F1514	Pass
Sound Transmission Class (STC)*	ASTM E90	53
Impact Insulation Class (IIC)*	ASTM E492	52
Delta IIC*	ASTM E2179	24
Floor Impact Sound	ASTM E3133	77.4 dBA

* Tested on a 6" concrete slab with no ceiling.

ecosurfaces.com • 833-888-1760

BUILT ON

itsTRU[®]

TECHNOLOGY

eco

surfaces