




ECOfit-Turf | ECOfit-Turf Plus



ECOfit-Turf and ECOfit-Turf Plus features a dense, textured 12mm thick polyethylene turf surface layer that is factory fusion bonded to a 5mm or 12mm composition rubber base layer. While too abrasive to fall or dive on, these surfaces are ideal for footwork drills and provide enhanced ergonomic support.

- Education
- Corporate
- Retail
- Public Buildings
- Hospitality

Benefits

- · No infill needed
- Ergonomic
- Acoustic
- Durable
- Portable / easy to install (ECOfit-Turf Plus tiles)
- Indoor only

Applications

- Functional Training
- Retail

Product Information

Nominal Dimensions:

Available as a standard in rolls and interlocking tiles. Talk to your local agent to determine availability, pricing, minimums, and lead times.



Rolls:

Available in 6' rolls.

Available in Green, Royal Blue, Black, and Gray.

ECOfit-Turf:

17mm (12mm + 5mm) x 72" (1.83m) x 35 LF (10.67m)

ECOfit-Turf Plus:

24mm (12mm + 12mm) x 72" (1.83m) x 25 LF (7.62m)



ECOfit-Turf Plus: 24mm (12mm + 12mm) x 23" (0.58m) x 46" (1.16m) Interlocking tiles are available with a coordinating interlocking transition system.



Interlocking Turf Reducer:

3/4" x 12" x 46"

Interlocking reducers are available for quick installation at room openings, or when area mat installations are required.

THE NRG FACTOR



ECOfit-Turf 30.8%

47.1%

ECOfit-Turf Plus Force Reduction Absorption of impact energy



Energy Restitution Useful return of impact energy







Safety

Ergonomics

Acoustics

More Information:

Click here to view ECOfit-Turf

Click here to view ECOfit-Turf Plus



Technical Details

Performance Criteria	Test Standard	Typical Results ECOfit-Turf ECOfit Turf Plus
Coefficient of Friction	ASTM D2047	>0.8 >0.8
Vertical Deformation	Deltec Field Tester	3.8mm 4.9mm
G-Max	Clegg	192 84
Tufted Pile Height		0.47" 0.47"
Flammability - Pill Test	ASTM D2859	Pass Pass



