







ECOsurfaces Adhesives Product Sales Sheet



Product	Available In	Type	Works With	Maximum RH (per ASTM F-2170)	Substrate pH	Flash Time	Working Time	Shelf Life	Freeze/ Thaw Stability	Antimicrobial	Trowel	Spread Rate
 ES-90	4 Gallon Pail	Moisture-cured Urethane	Vulcanized Composition Rubber Sound Control Underlayments	90%	≤12	0-10 minutes	20-30 minutes	1 Year when stored in original, unopened packaging at 73°F (23°C)	Stable	No	1/16" sq. notch	90 SF/gal
											1/8" sq. notch	45 SF/gal
											1/16" x 1/32" x 1/32" U-notch	120 SF/gal
 E-Grip 95	4 Gallon Pail	One-Part Urethane	Vulcanized Composition Rubber	95%	Max of 12	None	30-45 minutes	1 Year	Stable	Yes	1/16" x 1/32" x 1/32" U-notch	160 SF/gal
											1/16" sq. notch	115 SF/gal
 E-Grip 99	4 Gallon Pail	One-Part Modified Urethane	Vulcanized Composition Rubber	99%	5 to 14	LVT: 10-15 minutes	45 minutes	1 Year	Stable to 10°F (-12°C)	Yes	1/16" x 1/32" x 1/32" U-notch (LVT/LVP only)	135 SF/gal
			Vinyl and LVT over Concrete (not over rubber)			All other products: None					1/16" sq. notch	105 SF/gal
 E-TAK 99	4 Gallon Pail	One-Part Acrylic PSA	LVT, 2mm Sheet Vinyl, Sound Control Underlayments	Tacky (Pressure Sensitive Installations) LVT Only				1 year when stored in original/unopened packaging at 73°F (23°C)	Protect from Freezing	Yes	Porous/Rough Substrate	
				99%	≤12	30 minutes	Up to 2 hours				1/16" sq. notch	150 SF/gal
				Wet/Semi-Wet Adhesive Installations							Non-Porous/Smooth Substrate	
				95%	≤11	N/A	Up to 30 minutes				1/16" x 1/32" x 1/32" U-notch	210 SF/gal
 E-Grip Tape	29" x 131' Roll	Tape	Products under 8.5mm	80%	7-9	N/A	N/A	2 years from Ecore ship date	N/A	No	N/A	305 SF/roll
 ES-Evolve 85	4 Gallon Pail	One-Part Acrylic PSA	ECOsilence and LVT + LVP over ECOSilence	85%	≤8	Pressure Sensitive Installations: 30-60 min	Up to 120 minutes	1 Year when stored in original, unopened packaging at 73°F (23°C)	Protect from Freezing	Yes	1/32" x 1/16" x 1/32" U-notch	225 SF/gal (non-porous)
						Wet or Semi-Wet Installations: 0-30minutes					1/16" sq. notch	150 SF/gal (porous)
											1/16" sq. notch	120 SF/gal (over ECOSilence)

E-Grip III Cartridges are available in 28 oz cartridges for use when installing 1" and 2.5" ECOMax tiles with Quad Bloks. One 28 oz cartridge of E-Grip III is required for every 40 Quad Bloks (1" Tiles) or for every 28 Quad Bloks (2.5" Tiles).

*Note: for all adhesives, protect the finished installation from light traffic for at least 24 hours, heavy foot traffic for at least 48 hours, and from heavy rolling loads for at least 72 hours. There are no traffic limitations for E-Grip Tape; all types of traffic can occur immediately after installation. For more information, please see the Technical Data Sheet on the specific adhesive product pages at ecosurfaces.com.