

ECOsurfaces Classic



ECOsurfaces Classic is a distinctive vulcanized composition rubber surface. Available in traditional rolls and tiles, this resilient surface has beauty and brains! Featuring the durability and ease of maintenance associated with a hard surface, ECOsurfaces offers similar acoustic attributes to a soft surface.

Markets

- Education
- Corporate
- Retail
- Institutional

Applications

- Selectorized Strength
- Free Weights
- Cardio
- Therapy / Rehab
- Retail
- Public Spaces
- Entrances
- Childcare / Playzones
- Offices


Benefits


- Durable – features ECOguard coating, a factory-applied urethane coating, and should be cleaned with a pH-neutral cleaner, such as Ecore E-Cleaner
- Slip resistant
- Offers better acoustic properties than traditional resilient surfaces
- Sustainable

Product Information

Nominal Dimensions:

Available as a standard in rolls and tiles. Talk to your local agent to determine availability, pricing, minimums, and lead times.

 Rolls:
48" (1.22m) x 50 linear feet (15.24)
Thickness: 3.2mm

 Tiles:
24" (61cm) x 24" (61cm)
Thickness: 3.2mm

[View Colors](#)

Accessories:
• Ecore E-Cleaner

Technical Details

Performance Criteria	Test Standard	Typical Results
Recovery after Static Load (@400psi)	ASTM F970 Modified	0.005"
Coefficient of Friction	ASTM D2047	> 0.8
Abrasion Resistance	ASTM D3389	Pass
Impact Insulation Class (IIC)*	ASTM E492	48
Delta IIC*	ASTM E2179	19
FloorScore	CA 01350	Certified

* Tested on a 6" concrete slab with no ceiling.

THE NRG FACTOR

NRG

=

2.4%

Force Reduction

Absorption of impact energy

75.5%

Energy Restitution

Useful return of impact energy

Safety

Ergonomics

Acoustics

ecosurfaces.com • 833-888-1760

BUILT ON

itsTRU[®]

TECHNOLOGY

eco

surfaces