




ECOsurfaces Adhesives Product Sales Sheet

Product	Available In	Type	Works With	Maximum RH (per ASTM F-2170)	Substrate pH	Flash Time	Working Time	Shelf Life	Freeze/ Thaw Stability	Antimicrobial	Trowel	Spread Rate				
 ES-90	4 Gallon Pail	Moisture-cured urethane	Vulcanized Composition Rubber Sound Control Underlayments	90%	≤12	0-10 minutes	20-30 minutes	1 Year when stored in original, unopened packaging at 73°F (23°C)	Stable	No	1/16" sq. notch	90 SF/gal				
											1/18" sq. notch	45 SF/gal				
											1/16" x 1/32" x 1/32" U-notch	120 SF/gal				
 E-TAK 99	4 Gallon Pail	One-Part Acrylic PSA	LVT, 2mm Sheet Vinyl, Sound Control Underlayments	Tacky (Pressure Sensitive Installations) LVT Only				1 year when stored in original/unopened packaging at 73°F (23°C)	Protect from Freezing	Yes	Porous/Rough Substrate					
				99%	≤12	30-60 minutes	Up to 4 hours				1/16" sq. notch	150 SF/gal				
				Wet/Semi-Wet Adhesive Installations							95%	≤11	N/A	Up to 30 minutes	Non-Porous/Smooth Substrate	
				1/16" x 1/32" x 1/32" U-notch		210 SF/gal										
 E-Grip Tape	29" x 131 LF Roll	Tape	Products under 8.5mm	80%	7-9	N/A	N/A	2 years from ECOsurfaces' ship date	N/A	No	N/A	322 SF/roll				

*Note: for ES-90 and E-TAK 99, protect the finished installation from light traffic for at least 24 hours, heavy foot traffic for at least 48 hours, and from heavy rolling loads for at least 72 hours. There are no traffic limitations for E-Grip Tape; all types of traffic can occur immediately after installation.

For more information, please see the Technical Data Sheet on the specific adhesive product pages at ecosurfaces.com.