

ECOcomfort



ECOcomfort underlayment provides the perfect blend of flexibility and support beneath ECOsurfaces surfacing. Unlike traditional foam cushioning systems, its exclusive manufacturing technology ensures that it maintains its resilience for years.

Markets

- Corporate
- Hospitality
- Education
- Retail
- Fitness
- Healthcare

Applications

- Selectorized Strength
- Free Weights
- Olympic Style Lifting
- Functional Training
- Cardio
- Therapy / Rehab
- Public Spaces
- Offices
- K-12 / Higher Education

Benefits

- Durable
- Ergonomic
- Works beneath all ECOsurfaces floors, as well as carpet and resilient flooring
- Engineered for superior ergonomic comfort, reducing injuries, and fatigue

Product Information

Nominal Dimensions:

Available as a standard in rolls. Talk to your local agent to determine availability, pricing, minimums, and lead times.



- Rolls:
5mm (0.20") x 48" (1.22m) x 25 LF (7.62m)
- 12mm (0.50") x 48" (1.22m) x 25 LF (7.62m)
- 25mm (0.9") x 48" (1.22m) x 25 LF (7.62m)
- 32mm (1.3") x 48" (1.22m) x 25 LF (7.62m)



Safety



Ergonomics



Acoustics

Technical Details

Performance Criteria	Test Standard	Typical Results
Weight Per Square Yard Calculated		12mm = 10.5lb 25mm =21lb 32mm =26.25lb
Tensile Strength	ASTM D412	25lbs per square inch
Flexibility	ASTM F137	Pass 1/4" Mandrel

* Tested on a 6" concrete slab with no ceiling.