

ECOnights



ECOnights is the ideal athletic surface for corporate gyms and hospitality fitness centers. Its slip resistance and nominal 3/8" thickness make it a durable solution for high impact spaces. Delivering unmatched durability and design options, ECOnights was developed to enhance any high-energy athletic environment. Offering excellent slip resistance in both wet and dry conditions and superior durability, ECOnights offers you more than just the basic flooring for your fitness environment.

Markets

- Corporate
- Hospitality

Benefits

- Slip resistant wet or dry
- Sound and shock absorbent
- Fade resistant, wears well
- ECOguard coated

Applications

- Selectorized Strength
- Free Weights
- Common Areas
- Retail
- Public Spaces
- K-12 / Higher Education
- Childcare / Playzones

Product Information

Nominal Dimensions:

Available as a standard in rolls and tiles. Talk to your local agent to determine availability, pricing, minimums, and lead times.



Rolls:
48" (1.22m) x 25 (7.6m) linear feet
Thickness: 8mm (3/8") nominal



Tiles:
23" (580mm) x 23" (580mm)
Thickness: 8mm (3/8") nominal

Color Options:

[Click here to view colors](#)

Technical Details

Performance Criteria	Test Standard	Typical Results
Static Load Limit	ASTM F970	0.005"
Coefficient of Friction	ASTM D2047	> 0.9
Abrasion Resistance	ASTM D3389	<1g, 1,000 cycles
Pill Test	ASTM D2859	Pass
Impact Insulation Class*	ASTM E492	51
Delta IIC*	ASTM E2179	22
FloorScore	CA 01350	Certified

* Tested on a 6" concrete slab with no ceiling.

THE NRG FACTOR

NRG



10.97% Force Reduction
Absorption of impact energy



67.7% Energy Restitution
Useful return of impact energy



Safety



Ergonomics



Acoustics

