



ECOsurfaces is a distinctive vulcanized composition rubber surface. Available in traditional rolls and tiles, this resilient surface has beauty and brains! Featuring the durability and ease of maintenance associated with a hard surface, ECOsurfaces offers similar acoustic attributes to a soft surface.

Markets

- Education
- Corporate
- Retail
- Institutional

Applications

- Selectorized Strength
- Free Weights
- Cardio
- Therapy / Rehab
- Retail
- Public Spaces
- Entrances
- Childcare / Playzones
- Offices


Benefits


- Durable – features ECOguard coating
- Slip resistant
- Offers better acoustic properties than traditional resilient surfaces
- Sustainable
- ECOsurfaces features ECOguard, a factory-applied urethane coating, and should be cleaned with a pH-neutral cleaner, such as Ecore E-Cleaner.

Product Information

Nominal Dimensions:

Available as a standard in rolls and tiles. Talk to your local agent to determine availability, pricing, minimums, and lead times.

 Rolls:
48" (1.22m) x 50 linear feet (15.24)
Thickness: 3.2mm

 Tiles:
24" (61cm) x 24" (61cm)
Thickness: 3.2mm

Color Options:

[Click here to view colors](#)

Accessories:

- Ecore E-Cleaner

Technical Details

Performance Criteria	Test Standard	Typical Results
Static Load Limit	ASTM F970	0.005" (@400psi)
Coefficient of Friction	ASTM D2047	> 0.9
Abrasion Resistance	ASTM D3389	<1g, 1,000 cycles
Impact Insulation Class*	ASTM E492	48
Delta IIC*	ASTM E2179	19
FloorScore	CA 01350	Certified

* Tested on a 6" concrete slab with no ceiling.

THE NRG FACTOR

NRG

=

2.4%

Force Reduction

Absorption of impact energy

75.5%

Energy Restitution

Useful return of impact energy

Safety

Ergonomics

Acoustics

ecosurfaces.com • 833-888-1760

BUILT ON

itsTRU™

TECHNOLOGY

eco

surfaces